



SiReMa Hybrid H_6006 Transparent

Premium upcycling regranulate

PRODUCT DESCRIPTION

SiReMa Hybrid H_6006T (PCR 60%) MFI 0.6 g/10min – an advanced, triple-filtered material with the PCR content, characterized by exceptional homogenization.

TECHNICAL DATA - OVERVIEW

Applications	Blown/cast films (industrial and consumer) for agriculture, construction and packaging; blow moulding of selected articles; sheet and profile extrusion.
Type of plastic / Material:	LDPE
Recycled content (PCR)	> 60%
Source	Post-consumer, various sources
Colour	Transparent
Certificate	 

TECHNICAL DATA - PHYSICAL PROPERTIES

	Nominal Value (SI)	Unit	Test Method
MFI	0,4 - 0,8 (±0,2)	g/10 min (190°C/2,16 kg)	PN-EN ISO 1133
Density (base resin)	0,93 - 0,95	g/cm ³ w 23°C	PN-EN ISO 1183
Filtration	90	µm	-
Ash Content	<1%	%	PN-EN ISO 3451
Thickness	23 - 400	µm	-

PACKAGING

Standard packing	Size of pallet	Weight of full truck
Big bag, 1000 – 1250 kg and silo truck	1,20 x 1,20 m	Max. 24 000 kg netto

Revision date: 13.03.26r.